



Erosion & Sediment Control

Product Summary

Silt Sack is a sediment control device used to prevent silt and sediment from entering your drainage system by catching the silt and sediment while allowing water to pass through freely. Silt Sac can be used as a primary or secondary sediment control device to prevent failure of your drainage system due to clogging. It must be maintained on a regular basis to function properly.

Contact Details

bmpsupplies.com
sales@bmpsupplies.com
1.855.422.0066

SILT SACK

SPECIFICATION SHEET

Grab Tensile	ASTMD-4632 - 315 lb
Grab Elongation	ASTM-D-4632 - 15%
Wide Width Tensile	ASTM-D-4595 - 200/200 lb/in
Wide Width Elongation	ASTM-D-3786 - 12/8%
Mullen Burt	ASTM-D-3786 - 800 psi
Puncture	ASTM-D-4833 - 140 lb
Trapezoidal Tear	ASTM-D-4533 - 125 lb
UV Resistance	ASTM-D-4355 - 80% at 500 hr
AOS(1)	ASTM-D-4751 - 40 sieve
Permittivity	ASTM-D-4491- 0.70 sec-1
Flow Rate	ASTM-D-4491 - 50 gal/min/ft2

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.

SILT SACK

PRODUCT DIAGRAM

