



Erosion & Sediment Control

Product Summary

BMP's Catch Basin Donuts are designed to have the rainwater pond and filter into the catch basin near construction sites. Primary benefits of the catch basin include easy installation and even easier maintenance for your erosion control needs.

Contact Details

bmpsupplies.com
sales@bmpsupplies.com
1.855.422.0066

Canadian Patent:

#2,414,270

US Patent:


#7,070,691

CATCH BASIN DONUT HIGH FLOW

SPECIFICATION SHEET

Foam Cover Fabric	R 2283 HDPE Monofilament (High Density Polyethylene)
Body Fabric	Yellow PE Mesh High FlowFabric
Foam	4" Height Open Cell Foam
Grate Size	Fits grates: 24" x 16", 24" x 24" 21" x 18"
Grab Tensile	ASTM-D-4632 - 315 lb
Compressed Size	8" x 8" x 4"
Expanded Size	Varies depending on Part Number
Permittivity	5.84 (s-1)
Water Flow Rate	436+ gal/min/ft ²
Optional	CIF6048 Curb Inlet Filter for grates with Curb Inlets

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.




Canadian Patent: #2,414,270


US Patent: #7,070,691

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.


1) Remove the grate and set aside. Using a steel brush and/or scraper, clean the edge that supports the grate from dirt and grime;




2) Lay the Donut upside down on the road surface.



3) Place the grate upside down on the donut fabric



4) Loosely connect the webbing straps across the grate to the corresponding buckles. Individually slowly tighten the straps while tucking the corner fabric in toward the center.



5) Turn over and replace the grate into the grate frame.

