



Erosion Control Blanket

Standard – Single Net – Aspen Excelsior (SSNAE)

Manufactured for slopes 2:1 (H:V) and lower flow channels, this blanket provides immediate erosion control and supports rapid vegetation growth. Filled with high-quality aspen Wood Wool fibers, it helps retain moisture and stabilize soil naturally. Wood Fibers stitched into a single net on top, BMP-SSNAE provides an effective and cost-efficient solution to soil erosion and sedimentation control. Typical functional lifespan is up to 18 months, depending on site conditions and climate. Ideal for use in roadside ditches, embankments, and general landscaping.

Properties	Manufacture Designed Values
Width	8.0 ft (2.4 m) or 16 ft (4.4m)
Length	112.5 ft (34.29 m)
Area	100.0 yd ² (83.6 m ²)
Weight*	73.0 lb (33.1 kg)
Fiber Count	≈7,000 per yd ² (≈8,400 per m ²)
Fiber Length (80% min.)	≥6.0 in (≥15.2 cm)
Mass Per Unit Area (± 10%)	0.73 lb/yd ² (0.40 kg/m ²)
Net Openings	1.0 in x 2.0 in% (25.4 mm x 50.8 mm)
Fill	100% Wood Wool Aspen Excelsior (80% ≥ 6 inches)
Longevity	Medium Term - est. 18 months
Mass Per Unit Area	9.12 oz/sq/yd
Tensile Strength	MD - 6.8 lb/in XD - 6.3 lb/in
Thickness	0.411 in 1.06 cm
Light Penetration	20%
Water Absorption	255%
Unvegetated Bench-Scale Rain Splash and Runoff	Soil Loss Ratio† = 4.2 @ 2 in/hr Soil Loss Ratio† = 4.4 @ 4 in/hr Soil Loss Ratio† = 4.8 @ 6 in/hr C Factor ≤ 0.18
Unvegetated Bench-Scale Shear Stress	1.75 psf @ ½ in soil loss (84 Pa)
Seed Germination (ASTM Method)	330%

*weight is based on a dry fiber weight basis at time of manufacture

Shipping From:

#50-183073 RR 150,
Brooks, Alberta T0J 2A0
Canada, County of Newell

The values presented are based on performance data from products manufactured using equivalent materials and comparable erosion control blanket machinery. As BMP-SSNAE are produced using the newest state-of-the-art machine, final performance metrics may improve upon receipt of certified third-party laboratory results.

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.